

**SLF 130**  
**R290**



**FROZEN SNOW**



Self-contained ice maker - Granular system  
Daily production up to 72 kg

● Position n°



● Application fields

Hotel	●●●●●●●●●●	Fish market	●●●●●●●●●●
Restaurant	●●●●●●●●●●	Supermarket	●●●●●●●●●●
Fast food	●●●●●●●●●●	SPA	●●●●●●●●●●
Bar	●●●●●●●●●●	Medical	●●●●●●●●●●
Disco	●●●●●●●●●●	Industry	●●●●●●●●●●

● Features & Plus

- Granular ice
- Low consumption (1 liter water / 1 kg ice) - aircooled vers.
- Electromechanical functioning
- External structure AISI 304 Scotch Brite
- Evaporator AISI 304, auger AISI 303 made
- Air Cooling and Water Cooling systems
- Standard and special voltages
- Insulated retractable door
- ON-OFF switch
- Dust proof water basin
- Easy cleaning thanks to rounded surfaces
- External protective filter, removable, easy to clean
- Removable side panels
- Internal bin insulation HCFC free
- Model in Tropical Class + 43 ° C
- Conformity to RoHS directive
- Undercounter model

● Prod. 24h

Air temp.	Water temp.	Prod. 24h kg
10° C	7° C	72
21° C	15° C	65
32° C	21° C	52

**2 Years Warranty**

subject to limitations

● Certifications available for this model



[www.ntfice.it](http://www.ntfice.it)  
[info@ntfice.it](mailto:info@ntfice.it)



ntfice.it




# SLF 130 R290



## FROZEN SNOW



Self-contained ice maker - Granular system  
Daily production up to 72 kg



### • Connections

All measures are referred to the rear bottom-left corner (L-H-Ø)

- ① Water inlet:  
106 mm - 135 mm - 3/4"
- ② Water outlet:  
55 mm - 55 mm - 24 mm
- ③ Electrical connection:  
114 mm - 218 mm

### • Working conditions





- Location: Indoor

	Min	Max
Ambient temperature	+10° C	+43° C
Water temperature	+3° C	+32° C
Voltage	-10%	+10%
Water inlet pressure	1bar (14 psi)	6bar (84 psi)

### • Technical information

Production in 24h	65 kg
Store capacity, up to	10 kg
Cooling system	A - W
Refrigerant	R290
Standard voltage	220-240 V ~ 50 Hz
Electrical consumption	400 W
Fuse	10 A
Water consumption	A: 1 l/kg W: 5 l/kg
Sizes (L-P-H mm)	450 - 620 - 680
Sizes with pack (L-P-H mm)	505 - 675 - 850
Net weight	56 kg
Gross weight	64 kg
Finish	AISI 304 stainless steel, scotch brite

All the technical information must be considered at the following conditions:

			
Sizes without feet	Ambient temperature +21° C	Water temperature +15° C	Electrical consumption at +43° C (standard voltage)

Models and specifications are subject to change without notice  
Rev. 01 - Issued September 2019

